Sourcevel Sourcevel



MAY 2022

Table of Contents



Application..... Why the LP61-G..... **Specs, Characteristic** Vacuum System..... Litter Collection Syste Contact Us..... **LP61-G** options: Trailer conversion kit..... Spare wheel..... Hose extension..... Litter collector bags..... Bagless debris system - | Filter cartridge.....

Technical specs are subject to change without prior notice

•••••••••••••••••••••••••••••••••••••••	3
• • • • • • • • • • • • • • • • • • • •	4–5
s & Performance	5-21
	2-24
em25	5-29
• • • • • • • • • • • • • • • • • • • •	30
• • • • • • • • • • • • • • • • • • • •	. 6
• • • • • • • • • • • • • • • • • • • •	. 20
• • • • • • • • • • • • • • • • • • • •	. 23
	. 25
Kevlar bin	26
	28



Application

Ideal for hard-to-reach soiled areas such as windblown trash at landfill and transfer station fence lines, parking lots, parks, cycling trails and industrial sites.





Why the LP61-G?

- Powerful vacuum litter collector: 5 times more efficient than manual picking
- Patented straight-through suction compacts litter
- No fan to jam technology

Why the LP61-G





- Compact, lightweight, easy to use • 2 transport options:
 - standard pickup truck with 6-ft bed
 - tow behind trailer with standard hitch



Trailer attachment types available:

- 2 in. ball
- 1.78 in. ball
- pintle
- **Trailer** jack

Trailer wiring harness (4 pin)

Skid mount to trailer option (or the reverse) in 45 min



Dimensions

Skid Mount

- Length: 72 in. (1828 mm)
- Width: 47.2 in. (1198 mm)
- Height: 49.5 in. (1257 mm)
- Weight: 750 lbs (340 kg)

<u>Trailer Mount</u>

- Length: 130 in. (3300 mm)
- Width: 47.2 in. (1198 mm)
- Height: 57.5 in. (1460 mm)
- Weight: 952 lbs (425 kg)





- Heavy gauge steel body on a weilded
 1/4 in. (6.35 mm) structural steel frame
- Electrostatic powder-coated paint









- Model: Vanguard 400 / Briggs & Stratton
- Displacement: 408 cc (25 cu in.)
- Gross rated power: 10.4 KW (14 HP)
- Fuel type: Petrol (Gas) no diesel

0 / Briggs & Stratton c (25 cu in.) 0.4 KW (14 HP) s) - no diesel



Reason for the change:

- Manufacturer offers a 3-year warranty versus 2-years with Honda
- Vanguard offers more autonomy with max. fuel capacity 12 gal (45.4 L) versus Honda 6 gal. (22.7L)
- Honda does not have a ventilated gas cap operator must manually release gas tank pressure before using the machine
- Vanguard 400 has a less complicated assembly easier to maintain, less wiring
- Aftersales Vanguard parts less costly / more available than Honda

Some of the photos in this document and on our YouTube channel show the LP61-G with a Honda engine. Since April 2022, this engine has been replaced with the Vanguard 400 manufactured by Briggs & Stratton.

da (45.4 L) versus Honda 6 gal. (22.7L) Jally release gas tank pressure before

ntain, less wiring nda

Control Panel

Throttle: sets engine revolution

2

Choke: Set choke open and close for engine start-up

3

Recoil starter rope (not required if ignition key is used)





Emergency stop button

Ignition switch: rotary key switch controls ignition circuit of the machine











Oil inlet





Spark plug

Oil drain



15

Double Belt

Transmits engine power to the fan

Muffler

Suppresses engine noise





• Fuel type: gas (no diesel)

Fuel

Tanks

- Fuel capacity: Motor 1.6 gal. (6 L) + two tanks 10.4 gal. (39.4 L) Total = 12 gal (45.4 L)
- Ventilated gas cap: no need to release pressure prior to start
- Fuel consumption: 1.3 gal (4.9L) per hour



Battery

12-volt heavy duty battery for engine starter and beacon light



Lighting Package



Fully street legal

- Beacon
- 4 corner lights



Wheels





4-season radial tires
175/80 R 13
Spare tire for trailer mount option





- Vacuum rating: 2200 CFM
- Air Flow: 7700 ft/min (2347 M/min.)
- Vacuum fan diameter: 14 in. (365 mm)
- Bottom mounted fan: no litter comes in contact with the fan
- Straight-through suction system compacts litter 2:1 ratio



Vacuum System



Vacuum Hose

Diameter: 8 in. (203 mm)
Length: standard 25 ft. (7.62 m) including the handle
Optional hose extension:15 ft. (4.57 m) or 25 ft. (7.62 m)





24

Hose Support

360-degree rotating vacuum hose support arm allows easy displacement and positioning of the hose



Container and Bag

- Litter capacity: 50 gal. (190 L)
- Bag: quick change reusable bag



• Material: 16-gauge powder-coated steel

Note: off-theshelf bags not compatible with this machine



Bagless Debris System - Kevlar Bin

Optional Kevlar bin can be filled, then emptied into off-the-shelf bag



Litter Catch Cover

(for litter bags and Kevlar bin)

Prevents litter from falling to the ground when container door is opened



Catch Cover

Bag

Installed



Dust Control

0

2-Micron Interior Cylindrical Filter Cartridge (Optional)

- Offers additional dust control (for high pedestrian areas)
- Compatible with litter collector bags only, not Kevlar bin



Dust Control

Exhaust Filtration Bag

Retains fine particles and dust before clean air is expelled



To schedule a demo, request a quote, or for more information on the LP61-G portable vacuum:

S 855-651-0444 (USA/Canada) 450-651-0444 (International)



info@exprolink.com



www.madvac.com





awarded contract vendor #093021-EXP

