



 **Madvac**®

All-Terrain Litter Vacuum

LN50 (diesel)

Product Overview

www.madvac.com



Sourcewell 
Formerly NJPA

 **canoe**
procurement group of canada



Jan 2023

LN50 (diesel) options

Heated seat	13
Sunshield rooftop	14
Vacuum head	29
Wander hose.....	30
Litter collector bags.....	32
Bagless debris system	33
Water mist system	35
Fire extinguisher	36
Floor mounted heater.....	37
Tire flatproofing	41

Table of Contents

Applications / Customers / Attributes.....	3-5
Specs, Characteristics & Performance.....	6-23
Vacuum System.....	24-30
Litter Collection System.....	31-35
Safety, Comfort & Convenience.....	36-43
Contact Us.....	44

Technical specs are subject to change without prior notice



Application

From concrete to grass, the LN50 can tackle all types of urban terrain with ease.

- Parks and grass areas
- Sidewalks
- Bike and pedestrian lanes
- Parking lots
- Curb side
- Alleys
- Pathways
- Alongside buildings



Customers

- Cities & municipalities
- Outdoor cleaning contractors
- Airports & seaports
- Transit authorities
- Healthcare services
- Distribution centers
- Shopping malls
- Educational & sports facilities
- Manufacturing facilities
- Amusement parks
- Casinos
- Military
- Correctional facilities





Attributes

- LN50 replaces **6 to 8** manual litter pickers (equal quantity of litter removed within same time period)
- Can collect litter that is dry, humid, or wet
- All-terrain vehicle
- Easy to operate, no CDL required
- Street legal lighting package

Dimensions

LN50




Inches to mm

10	254
40	1016
48	1219
49	1245
69	1753
92	2337
95	2413
108	2743


Dimensions

7

WANDER
HOSE




Inches to mm
13 330




Dimensions

VAC HEAD




Inches to mm
11 279



Dimensions

9

WANDER
HOSE
+
VAC
HEAD



Inches to mm
132 3353



Ground Clearance & Curb Climbing

Curb climbing:
7 in. (178 mm) tall

Weight

- Net/dry weight: 2579 lbs (1170 kg)
- Gross vehicle weight rating: 3150 lbs (1429 kg)
- Axle rating:
front 1980 lbs (898 kg)
rear 1980 lbs (898 kg)





Frame & Body

Heavy gauge steel
body on a welded
1/4 in. (6.35 mm)
structural steel
frame

Electrostatic
powder-coated
paint

Cabin

Cabin size: 48 cu. ft. (1.36 cu. m.)



Seating: 40.5 in. (1029 mm) above ground



- Armrest, headrest, and optional heated seat for operator comfort
- Grab-handle and cup holder
- One safety lap belt
- Automotive-type steering wheel with steering ball for ease of handling

Sunshield Rooftop

Optional
sunshield helps
operator stay cool





Engine

- Model: Kubota Diesel D1105-E4B (EPA Tier 4 Final)
- Power: 24.8 hp (18.5 kw) @ 3200 rpm
- Displacement: 68.53 cu.in. (1123 cc)
- Air cleaner: 2-stage Donaldson with restriction indicator



General Machine Performance

- Max. forward speed: 11 mph (18 km/h)
- Max. reverse speed: 5 mph (8 km/h)
- Min. aisle turn: 180 in. (4572 mm)
- Internal turning radius: 60 in. (1524 mm)
- External turning radius: 90 in. (2286 mm)
- Cleaning speed:
up to 84,480 sq. ft. per hour
- Gradeability: 11.3 deg. (20%)
(with full & empty litter container)

Instrumentation & Controls

- Turn signal/horn/beacon/work light switch and lever
 - Fuel gauge
 - Operator presence indicator
 - Parking brake indicator
 - Left/right signal indicator
 - Engine oil pressure indicator
 - Engine temperature light
 - Hourmeter
 - Glow plug indicator
 - Hazard light switch
 - Low voltage indicator light
- (...continued on following page)



Instrumentation & Controls

- Key ignition for starting and stopping the engine
- Key ignition glow plug on prior to starting the engine
- Neutral start switch installed on traction control pedal prevents engine from starting if pedal is pressed
- Brake pedal on opposite side of steering column
- Throttle: progressive lever (idle up to maximum operating speed)
- Steering: adjustable tilt steering column



Drive

- Drive: front wheel drive
- Drive system: heavy-duty hydrostatic
- Turf size (all 4 wheels)
 - Regular: 20.5x8x 10 in. / 520x203x254 mm (205/65-10)
 - Turf MV17094: 20x8x10 in. / 508x203x254 mm (205/60-10)
- Tire load capacity: 1323 lbs / 600 kg per tire
- Brakes: front hydrostatic brake; rear mechanical disc parking brake
- Suspension: leaf spring front & rear





dB Rating

Front decibel

- Cabin: 96 dB
- 5 feet away: 88 dB
- 10 feet away: 85 dB
- 20 feet away: 83 dB

Lighting

Complete road lighting and signaling package

- Strobe beacon
- LED headlight
- LED turn signals
- LED brake lights
- LED flashers
- LED backup lights (with backup alarm)
- License plate holder with light
- SMV emblem



Fuel Tank

Capacity: 10.2 gal. (39 L)


Can easily do an 8-hour shift



Capacity: 12.5 gal. (47 L)

Hydraulic Oil Tank

*Easily accessible with see-through
oil level indicator*



Vacuum Fan & Suction System

- Straight-through suction system compacts litter 2:1 ratio
- No litter comes in contact with the fan
- Vacuum rating 1800 CFM



Vacuum fan position: bottom mounted



Vacuum fan diameter: 14 in. (356 mm)

Vacuum Hose

- Diameter: 7 in. (178 mm)
- Right-side support for hose storage in transport mode
- 160-degree arm movement with 50 in. (1270 mm.) reach
- Bottom of suction hose maximum lift above ground surface: 26 in. (660 mm)



Vacuum Hose Support Arm

For operator safety and easy displacement of the boom | removable plate to access top hose



Vacuum Arm Control

Hydraulic assist up/down movement of the boom for effortless displacement
4-button joystick control for up / down / vacuum fan ON / vacuum fan OFF






Mirrors

2 convex mirrors mounted
on vacuum arm with 340-
degree rear visibility





2 operating positions : one on each side of vacuum head

Vacuum Head

Optional

Effortless vacuuming, simply drive over litter



Wander Hose

Optional

*For confined,
hard-to-reach
areas*

Length: 15 ft. (4.57 m)
Diameter: 6 in. (152 mm)



Container


One bag

One container

Easy, Fast, Efficient

- 16-gauge powder-coated steel container
- Air cylinder power-assist tilt
- Litter capacity
 - Volume: 75 gal. (284 L)
 - Weight: 150 lbs (68 kg)





Bag size: 42 x 51 in.
(1066 x 1295 mm)

Litter Bags

*One container, one bag -
easy bag changing process
that takes only 45 sec!*

Bagless Debris System: Kevlar Bin



Optional Kevlar bin can be filled, then emptied into off-the-shelf bag or dumpster

Dust Control

Exhaust bag captures dust particles that can escape from the minute holes of the special Madvac collector bags or Kevlar bin








Dust Control

Optional intermittent water mist system with 10.17 gal. (38.5 L) water tank: controls dust and reduces risk of cigarette butt fire inside the container



Safety





Foot Heater

Optional 2-speed floor-mounted heater keeps operator's feet warm during cold weather

Console Accessory Box


Console accessory box with
USB / 12V aux outlet and switch
for optional floor heater and
optional water mist system





Foot Step

Helps operator
climb on board
easily and safe



Foot Activated Horn

Allows the operator to use the horn while keeping one hand on the steering wheel and the other controlling the vacuum arm

Convenience



Broom and rake holder



License plate holder




Tire flat proofing -
liquid sealant (optional)



Tilt seat for engine compartment



Easy access to all critical components of the machine



Easy access to all
critical components
of the machine

Hinged side door
for oil cooler
and radiator



Contact

To schedule a demo, request a quote, or for more information on the MADVAC LN50 diesel all-terrain litter vacuum:



855-651-0444 (USA/Canada)
1-450-651-0444 (International)



info@exprolink.com



www.madvac.com

 **Excelway**®

 **Madvac**®

2 Brands, ONE Great Company

 **exprolink**

Sourcewell 
Formerly NJPA

 **canoe**
procurement group of canada

awarded contract vendor **#093021-EXP**